



800-558-2240 (Samples)
800-366-2689 ext. 2706 (Tarkett Commercial Technical Assistance)
FAX: 713-869-5271 (Tarkett Commercial Technical Assistance)

Technical Assistance E Mail: AzTech@Tarkett.com

SECTION 09.65.19.00

COMMERCIAL HOMOGENEOUS TILE

PART 1 - GENERAL

1.01 SECTION INCLUDES

- A. Provide commercial homogeneous tile flooring with accessories, as required for complete installation.

1.02 SUBMITTALS

- A. Product Data: Furnish manufacturer's literature for each type of material to be provided for Project.
- B. Samples: Furnish each type of tile and edge strip required for Project.
- C. Color Charts: Show full range of colors and patterns available.

1.03 QUALITY ASSURANCE

- A. Installer Qualifications: Firm with minimum five years successful experience completing resilient tile installation similar to that required.

1.04 SITE CONDITIONS

- A. Maintain minimum 65 degree F air temperature at flooring installation area for minimum two days prior to, during, and for minimum 24 hours after installation of resilient tile.
- B. Store flooring materials in area of application; allow two days for material to reach same temperature as area. and maintain for minimum 24 hours after completion of installation.

PART 2 - PRODUCTS

2.01 MATERIALS

- A. Commercial Homogeneous Tile Manufacturer: Azrock, a brand of Tarkett Commercial Flooring, Telephone 800-558-2240 (samples) and 800-366-2689 ext. 2706 (Azrock Technical Assistance); Fax 713-869-5271 (Azrock Technical Assistance). E-mail Technical Assistance: AzTech@Tarkett.com
- B. Type: Azrock/Commercial Homogeneous Tile, ASTM F 1700 Solid Vinyl Floor Tile; 1/8 inch gauge; minimum 0.45 CRF per ASTM E 648; maximum smoke density of 450 per ASTM E 662; static load limit of 800 psi or higher; minimum slip resistance rating of > 0.60, Quality Assurance, latest ISO 9000 Standard.
- C. Colors: As selected by Architect from manufacturer's full range of colors.
 - 1. Milano, 16 inch by 16 inch (12 colors).
 - 2. Milano SR, 16 inch by 16 inch (5 colors), slip resistance rating of 0.8.
 - 3. Cortina Grande, 16 inch by 16 inch (24 colors).
 - 4. Cortina Grande SR, 16 inch by 16 inch (5 colors), slip resistance rating of 0.8.
 - 5. SolidAire, 16 inch by 16 inch (20 colors).
 - 6. Karim Kolors, 16 inch by 16 inch (6 colors)

Specifier Note: All products are available by special order, minimum 300 carton run, with special size, shape, surface and edge affects. Select and incorporate from the following choices available:

Added Dimensions (Options)

Size: 16 inch by 16 inch, (12 inch by 12 inch)

Shape: "Node", "Wave", "Tri", "Hive"

Grout: 1/8 inch- 2 sided Grout-Fit

Textures: Rustic Stone, (Slate)



800-558-2240 (Samples)
800-366-2689 ext. 2706 (Tarkett Commercial Technical Assistance)
FAX: 713-869-5271 (Tarkett Commercial Technical Assistance)

Technical Assistance E Mail: AzTech@Tarkett.com

- D. Accessories: Provide vinyl edge strips (moldings), subfloor hydraulic/Portland cement filler, primers, adhesives, and floor finish as required for complete installation; edge strip (molding) colors as selected to compliment flooring.

PART 3 - EXECUTION

3.01 PREPARATION

- A. Comply with manufacturer recommendations for preparation of substrate.
1. Concrete, Terrazzo, Latex Patching Compound Floors: Comply with ASTM F 710 in addition to manufacturer recommendations for preparation of substrate.

3.02 INSTALLATION

- A. Comply with manufacturer's recommendations and installation instructions.
B. Install minimum 1/2 tile at room and area perimeter.
C. Install edge strips (moldings) at unprotected and exposed edges where flooring terminates.
D. Fit flooring to walls, columns, floor outlets and other appurtenances, to produce neat joints.
E. Consult with Architect for floor pattern desired in each area.

3.03 CLEANING AND POLISHING

- A. Clean floors taking care not to wash floors prior to adhesive set.
B. Apply floor finish in accordance with manufacturer's recommendations.

END OF SECTION