



Product Data Sheet

Granite™ – Premium Vinyl Composition Tile

Technical data		
Type of floor covering		Premium Vinyl Composition Tile
ASTM F 1066		Class 2 Through Pattern
Smoke Density	ASTM E 662	<450
Flammability	ASTM E 648	Class 1 >0.45 CRF
Static load limit	ASTM F 970	150 psi
Slip Resistance	ADA Compliant	>0.6 COF
Recycled Content		Minimum 5% post-consumer / 9% pre-consumer
Thickness		1/8" / 3.2 mm
Colors		7
Tarkett Trowel Adhesive		100 Clear Thin Spread (VOC <1 g/l)
Tarkett SpraySmart Adhesive		122SG Gold
Warranty		5 Year Manufacturing 5 Year limited moisture/PH if installed with SpraySmart
Maintenance		Conventional VCT maintenance / 5+ coats of finish*
Tile Size		12" x 12" / 30.5 cm x 30.5 cm
Quantity		45 tiles per ctn - 45 sq. ft. (4.18 m ² per ctn)
Weight		65 lbs per ctn (29kg)

* Depending upon use of the floor.

Visit www.Azrock.com to download LEED matrices.
Click on Environmental Section - LEED Matrices.



All of our plants are ISO 9001 and ISO 14001 Certified.



2728 Summer Street . Houston, Texas . 77007

www.azrock.com