



800 PRESSURE SENSITIVE ADHESIVE

TYPE: Acrylic Latex Emulsion/Dry Set

COLOR: Off-white

INSTALLATION SYSTEMS: Solid Vinyl Tile

SUBFLOORS: Concrete (all grades), terrazzo, ceramic, marble, polymeric poured floors, suspended plywood, and over existing single layer vinyl composition, vinyl asbestos, and asphalt tile firmly adhered to approved subfloors.

FEATURES: Zero T.V.O.C., fast drying, low odor, plasticizer migration resistant, excellent grab, moisture and alkali resistant.



LEED RECOGNITION:

CRI Green Label Plus, Certified Low Emitting Product.

CONTAINER SIZES AND PACKAGING:

1 Gallon pail (3.78 L)(4/case)	Weight 36 lbs. (16.2 Kg) per case
4 Gallon pail (15.14 L)	38 lbs. (17.1 Kg)

TROWEL SPEC & COVERAGE:

1/32" (0.8mm) deep, 1/16" (1.6mm) wide, 1/32" (0.8mm) apart.
300 sq. ft. per gallon (25 M² per 3.78 L)

DRYING TIME: 45 minutes to 1 hour, depending on temperature, relative humidity, and porosity of subfloor.

OPEN TIME: Up to 6 hours, depending on temperature, relative humidity, and porosity of subfloor.

FREEZE THAW STABLE: Yes, to 0°F (-18°C), up to 3 cycles

OSHA: Non-combustible	DOT: N/A	
HMIS Health-	1 Flammability-	0
Reactivity-	0 Personal Protection-	B

APPLICATION: First apply the adhesive with the specified notched trowel in a thin, uniform, and even coat. Allow adhesive to dry until it loses its milky appearance and does not transfer to finger when touched. When dry, adhesive is extremely tacky. Lay tile into dried film, positioning carefully, because it will be difficult to slide the tile. For best adhesion, roll installed tile with 100 lb. (45 Kg) three-section roller. Close container between spreading cycles after each use.

CLEAN-UP AND STORAGE: Use water to remove wet adhesive from tile or tools. Use mineral spirits with caution to remove dried adhesive. Excessive use of mineral spirits will destroy bond. Store at moderate temperatures. One year when stored in original containers at temperatures between 65°F (14°C) to 85°F (30°C) in a dry area.

CURING AFTER INSTALLATION: Do not place furniture or allow traffic on newly installed floor for 48 hours. Allow at least 5 days under recommended conditions for tile and adhesive to achieve bond prior to commencing recommended initial maintenance routine.

For additional information consult adhesive label and if used in the workplace obtain a Material Safety Data Sheet. For subfloors and conditions not covered contact your local Representative or **Tarkett's** Commercial Tile Installation Services Department for the specific guidelines.