



Spray Smart Adhesive: 121 Platinum 10/12

TECHNICAL DATA SHEET

Advantages

Self-contained system spray that is recommended for installation of Commercial Vinyl Enhanced and Homogeneous Vinyl Tile. Available in 28 pound commercial cylinders & 22 ounce bottles.

Adheres To These Surfaces

- Concrete
- Existing VCT
- Wood
- Metal

Product Benefits

- Saves time- Spray vs. Trowel
- No buckets to carry in or dispose of
- No pre mixing required
- Water-based- No hazardous solvents/emissions, Zero VOC's
- Non-toxic, Non-flammable
- Adheres to both porous and non-porous surfaces
- Excellent for water vapor emissions and alkali tolerance 10lbs/1000 sq. ft. /12pH
- Floor may be maintained & used immediately after installation is completed
- Easy clean up
- Long open time
- Dries fast once surfaces are bonded
- No trowel marks

LEED RECOGNITIONS:

- CRI Green Label Plus, Certified Low Emitting Product
- Floor Score, Certified Low Emitting Product



Additional Advantages

- Self-contained system
- No trowels
- No waste
- Apply standing up

Coverage

28 pound cylinder- 2500 sq. ft. / 235 sq. m. 22 ounce bottle- 100 sq. ft. 10 sq. m.

Cleanup

Wipe excess adhesive off of spray tip while the adhesive is wet or dry. Clean hands or over-spray areas with Multi-Purpose Cleaner. Wipe off over-spray areas with water-damp cloth before adhesive dries.

Storage

Product shall ideally be stored in a location that is dry and between 46° to 82° F (8° to 28° C), ambient temperature. Optimal storage is at the middle of the range. **NOT FREEZE THAW STABLE**

Caution

Contents under pressure. Store at room temperature. Avoid freezing temperatures or exposure to more than 120° F (48° C). Keep out of reach of children. Avoid spraying on skin, face of eyes. Do not concentrate vapors or inhale fumes. Use only with proper ventilations.